

U/UTP CAT5E CABLE



ITEM NO .

- 5 Enhanced U/UTP AWG24

TEST STANDARD

- ISO/IEC 11801, TIA/EIA 568C.2

CONDUCTOR

MATERIAL

- Solid Bare Copper

NOM.O.D.

- 0.50 ±0.03mm

INSULATION

MATERIAL

- HDPE

NOM.O.D.

- 0.90 ±0.003

JACKET

THICKNESS

- 0.55 ±0.05mm

EXTERNAL O.D.

- 5.0 ±0.3

MATERIAL

- PVC
- LSZH
- PE

COLOR

- As required

ELECTRICAL

CHARACTERISTICS (20)

- Impedance() 100 ±15
- Delay Shew(ns/100m) 45
- NVP 69%
- Capacitance(nf/100m) 5.6
- DC Resistance(/100m) 9.5
- DC Conductor Resistance 5.0
- Unbalance(%)

RIP-CORD

- Yes

DRAIN WIRE

- No



PLASTIC REEL & PULL CARTON



DIMENSION

35*35*21cm

LENGTH

305 ±1.5m

WOODEN REEL & CARTON




DIMENSION

33*33*30cm

LENGTH

300 ±2.5m



TECHNICAL PERFORMANCE(100M):

FREQUENCY (MHz)	RL dB	ATT(20°) dB	NEXT dB	ACR dB	FREQUENCY (MHz)	PSNEXT dB	ELFEXT dB	PSELFEXT dB
1.0	20.0	2.0	65.3	63.3	1.0	62.3	63.8	60.8
4.0	23.0	4.1	56.3	52.2	4.0	53.3	51.8	48.8
8.0	24.5	5.8	51.8	46.0	8.0	48.8	45.7	42.7
10.0	25.0	6.5	50.3	43.8	10.0	47.3	43.8	40.8
16.0	25.0	8.2	47.2	39.0	16.0	44.4	39.7	36.7
20.0	25.0	9.3	45.8	36.5	20.0	42.8	37.8	34.8
25.0	24.3	10.4	44.3	33.9	25.0	41.3	35.8	32.8
31.25	23.6	11.7	42.9	31.2	31.25	39.9	33.9	30.9
62.5	21.5	17.0	38.4	21.4	62.5	35.4	27.9	24.9
100	20.1	22.0	35.3	13.3	100	32.3	23.8	20.8

JACKET PHYSICAL PROPERTIES

JACKET

AGING				COLD BEND	
ITEM	AGING PERIOD	100°*24H*7D	100°*24H*7D	COLD PERIOD	-20 ±2°C*4H
	Before Aging	After Aging		Bend Radius	8*Cable O.D.
PVC	Tensile Strength	13.5 Mpa	12.5 Mpa	No Visible Cracks	
	Elongation	150 %	125 %		
LSZH	Tensile Strength	10.0 Mpa	8.0 Mpa	No Visible Cracks	
	Elongation	125%	100%		
PE	Tensile Strength	10.0 Mpa	8.0 Mpa	No Visible Cracks	
	Elongation	350 %	350 %		

P/N	DESCRIPTION
UU5.50.PV - E	Cat5E U/UTP AWG24 PVC Jacket CPR class Eca
UU5.50.LS - E	Cat5E U/UTP AWG24 LSZH Jacket CPR class Eca
UU5.50.PE - E	Cat5E U/UTP AWG24 PE Jacket CPR class Eca
UU5.50.PVPE - F	Cat5E U/UTP AWG24 PVC + PE Jacket CPR class Fca
UU5.50.LS - D	Cat5E U/UTP AWG24 LSZH Jacket CPR class Fca

Special Jackets in accordance with customer's requirements